

63mm Mikronwood Venetian



MIKRONWOOD™ delivers an exciting new dimension to Composite Timber Venetian Blinds. The composite used in these blinds is widely used across the USA.

Tested by weather extremes as window and door frames as well as outdoor decking, this product provides a level of toughness not previously seen in the Composite Blind Market.

The SuperCap™ tough bonded surface offers standout quality and durability. Choose the best features of Timber and Vinyl and MIKRONWOOD™ is the answer.

Available Sizes

Width:

Maximum recommended width is 2400mm.
 Absolute maximum width is 2700mm.
 Absolute minimum width is 180mm.
 Blinds 180mm-260mm will have filter only in the middle and no cord lock.
 Blinds 260mm-390mm will have cord lock and filter at opposite ends."

Maximum Area under Warranty:

4 square metres

Head Box

Width:

56mm

Height:

52mm

Thickness:

0.5mm

Material:

Roll formed steel, painted

Colour:

White, Magnolia, Camel, Dark Brown

Bottom Rail

Width:

46mm trapezoid shaped

Height:

16mm

Material:

Composite with a SuperCap™ tough bonded surface

Colour:

Identical to blade colour

Fascia

Height:

Colonial 63mm (standard)
 Federation 90mm

Thickness:

10mm

Width:

Maximum width is 2700mm

Material:

Composite with a SuperCap™ tough bonded surface

Colour:

Identical to slat colour

Brackets:

Zinc plated Steel Reveal or Face Fit brackets

Blade Sizes

Width:

63mm

Thickness:
3.1-3.2mm

Material:
Composite with SuperCap™ tough bonded surface

Cloth Tape Ladders Colour:
Limited colour range (Turnils)

Cloth Tape Ladders Optional:
Yes

Plastic Tape Ladders Optional:
No

Cords

Dimensions:
2.2mm diameter with reinforced core

Material:
100% Polyester, heat set, non-stretch

Colour:
Co-ordinated with blade colour and ladders

Control Cords Length:
750mm unless specified

Cord Holes:
3.3mm x 27.9mm

End Spacing:
150mm to the first cord for widths above 600mm

Tilt and Lift Components

Mechanism:
Pull Cord Operation to open and close.
Polyoxymethylene with Zinc heavy duty Gear for reliable operation

Tiltrod:
6mm square steel tiltrod attached to the filter mechanism.

Cord Lock

Material:
Zinc coated steel case with polymethylene rollers

Colour:
Silver

String Ladders

Rung Width:
66mm

Pitch:
56mm

String Ladders Standard:
Yes

Installation Brackets

End Mounted:
Powdercoated steel

Centre Support:
Powdercoated steel

Spring Loaded Centre Support:
Zinc coated steel

Cloth Tape Ladders

Cloth Tap Ladders Rung Width:
66mm

Cloth Tape Ladders Pitch:
25mm

Cloth Tape Ladders Material:
100% Polyester, yarn dyed, heat set

Bottom Rail Hold Down:
Zinc plated or gold plated steel

Available Colours

Aspen, Fleece, Polar Cottage Pine, Golden Oak, Limestone, Pebble

Stacking Height

Drop of Blind	String Ladder Stacking Height	Ladder Tape Stacking Height
500mm	92mm	107mm
1000mm	119mm	144mm
1500mm	146mm	181mm
2000mm	173mm	218mm
2500mm	200mm	255mm
3000mm	227mm	282mm

Child Safety

Breakaway tassels are fitted to each blind so that they will separate into two pieces when pressure is applied to the cords.

Cleats are also supplied to ensure that the cords can be tied up out of the way when the blind is pulled up.
