

Convertible Awning

Convertible Rope Operated Awnings are the most popular 'easy to operate' awning, providing a cost effective shade for windows at all heights - ground floor, first and second storey. Rope operation can be tied off externally down the wall to a cleat or winch operation; or internally to a shutter winch. Alternatively, motorisation is available with switch operation or remote control. Sunlight Products sources an extensive range of Fabrics from all of the major suppliers to the awning industry. An optional awning hood is available in a decorator range of colours, complementing the overall appearance of the awning as well as helping to protect the fabric when the awning is not in use.

Available Sizes

Width:

Maximum Width – 4200mm
Minimum Width – 600mm

Drop:

Maximum Drop – 3000mm
Minimum Drop – 600mm

Maximum Area under Warranty:

10 sq metres

Headbox (optional)

Material:

Colourbond Steel

Headbox Ends Material:

Colourbond Steel

Available Colours:

Black, Dark Brown, Dark Green, Heritage Red, Merino, Mist Green, Mountain Blue, Primrose, Slate Grey, Wheat, White

Top Roller Keyway Tube

Material:

Galvanised Steel

Colour:

Silver

Available Sizes:

50mm, 63mm diameter in top pocket

BottomRail

Shape:

20mm, 25mm waterpipe in bottom pocket

Material:

Galvanised Steel, Silver

Standout Arms

Material:

Zinc Plated Steel

Colour:

Silver

Available Sizes:

1/2 drop of awning unless you specify.

Standard available sizes are:

609mm, 685mm, 762mm, 838mm, 914mm, 990mm, 1066mm, 1143mm, 1219mm, 1371mm, 1524mm, 1676mm, 1828mm.

Mounting Brackets

Type:

Face Fit Tail Bracket (standard), Reveal fit Bracket, Long Out Bracket, Ceiling Fix Bracket

White, Black

Material:

Cast Aluminium, Zinc Plated Steel

Pivot Arm Wall Bracket**Material:**

Face fix, Reveal fix - Cast Aluminium

Colour:

Silver

Colour:

Silver

Rope Spool**Material:**

Cast Aluminium

Tape Operation Shutter Winch and Winch Handle**Optional extra:**

Shutter Winch can be used with flat tape instead of 6mm rope and cleat; for internal control awnings.

Colour:

Silver

Tape Operation Rua Winch**Optional extra:**

RUA Winch must be used with flat cord operation instead of 6mm rope and cleat.

Available Sizes:

To fit 50mm, 63mm roller tube

Tape Spool**Material:**

Cast Aluminium

Rope Operation Winch**Optional extra:**

Boat winch can be used externally with rope operation

Colour:

Silver

Available Sizes:

To fit 50mm, 63mm roller tube

Motorisation**Optional extra:**

240V AC; Somfy LT50 and LT60 tubular motors are mounted inside 50mm, 63mm roller tubes. Switch operated or remote control are available.

Idler End Plug

Galvanised

Cords**Dimensions:**

6mm

Available Fabrics

Addalong Canvas, Brella Canvas, Hunter Douglas Canvas, Dickson, Planasol, Solaire, Docril, Sun Brella, Outlook, Vistaweave, Shadeview, Visiontex

Material:

Polypropylene

Colour: