

System 2000 Pivot Arm Awning



System 2000 Pivot Arm Rope/Cord operated Awnings are especially ideal for cladding and fibro style applications, where fixing is not required at the very ends of the awning, as it is with the standard Convertible Cord/Rope operated Awning. Provided the awning is installed with a hood, fixing points for the System 2000 Pivot Arm Awning can be located anywhere along the full width of the awning hood at the top, as also can the fixing of the pivot arms be positioned anywhere along the bottom rail. Rope operation can be tied off externally down the wall to a cleat or winch operation; Tape operation for internal operation can be tied off to and internal cleat, tape box or shutter winch. Alternatively, Motorisation is available with switch operation or remote control. Sunlight Products sources an extensive range of Fabrics from all of the major Fabric Suppliers to the awning industry. System 2000 Awning Hoods are available in a decorator range of colours complementing the appearance of the awning as well as protecting the fabric when not in use.

Available Sizes

Width:

Minimum Width – 600mm

Maximum Width

- 2510mm for Tape Operation

- 3600mm for Tape Winch Operation

- 4200mm for Rope Operation

- 3500mm for Crank Operation

Drop:

Minimum Drop – 600mm

Maximum Drop

- 1800mm for Tape Operation
- 2100mm for Tape Winch Operation
- 2400mm for Rope Operation
- 2000mm for Crank Operation

Maximum Area under Warranty:

- 4.3 sq metres for Tape Operation
- 7.5 sq metres for Tape Winch Operation
- 10 sq metres for Rope Operation
- 7 sq metres for Crank Operation

Headbox (optional)

Material:

Zincalume, Steel

Headbox Ends Material:

Nylon reinforced with glass

Available Colours:

Anvil, Black, Federation Green, Galaxy, Mist Green, Primrose, Red Oxide, Stone Beige, White, Woodtone

Headbox Mounting Brackets

Material:

Wall Brackets, Zinc Plated Steel

Colour:

Silver

Top Roller Keyway Tube

Material:

Galvanised Steel

Colour:

Silver

Available Sizes:

60mm diameter

Bottom Rail

Shape:

5 sided

Material:

Colourbond Steel

Available Colours:

Anvil, Black, Dark Brown, Dark Green, Merino, Mist Green, Mountain Blue, Primrose, Wheat, White, Galaxy, Stone Beige

Material:

Grey Plastic

System 2000 Bottom Rail Snap On Bracket**Material:**

Nylon

Colour:

Grey

Rope Spool**Material:**

Plastic / Metal

Colour:

Grey

Available Sizes:

To fit 60mm roller tube

Tape Spool**Material:**

Plastic / Metal

Colour:

Grey

Available Sizes:

To fit 60mm roller tube

Idler End Plug

Grey PVC

Standout Arms**Available Sizes:**

1/2 drop of awning unless you specify.

System 2000 Arm Tube**Material:**

Anodised Extruded Aluminium Tube

Colour:

Silver Anodised

Available Sizes:

1/2 drop of awning unless you specify

Mounting Brackets**Type:**

Universal Auto Bracket (if hoods are not required)

Material:

Zinc Plated Steel

Colour:

Silver

Pivot Arm Wall Bracket**Material:**

Face fit only - Zinc Plated Steel

Colour:

Silver

System 2000 Spring Set:

Supplied with each pivot arm

Tape Operation Shutter Winch And Winch Handle**Optional extra:**

Shutter Winch can be used with flat tape instead of Tie off Cleat or Tape Box.

Tape Operation**Tape Guide:**

Black Plastic

Swivel Tape Guide:

Natural Plastic

Swivel Tape Plate:

Natural Plastic

Plate For Lift Tape Lock:

Natural Plastic

Lift Tape Lock:

Silver Metal

Tassel:

Grey Plastic

System 2000 Gear/Crank Operation**Optional extra:**

System 200 Pivot Arm operated by Gear Mechanism and Crank handle 1800mm.

Rope Operation Winch**Optional extra:**

Boat winch can be used externally with 6mm rope operation.

Motorisation**Optional extra:**

240V AC, Somfy LT50 and LT60 tubular motors are mounted inside 60mm roller tubes. Switch operated or remote control are available.
