

## Wire Guide Awning



The Wire Guide Awning provides a great contemporary shading solution externally, for large spans of glass, large verandah and patio areas. The Wire Guide awning features highly polished and corrosion resistant stainless steel fittings along with stainless steel cabling which suspends and secures the awning on either side, so that it is capable of withstanding light to medium strength winds. Multiple bracket sizes and glass filled nylon endcaps add extra stability. The slimline bottom rail creates a minimalist look for the overall appeal of the awning. Ideal for Sunscreen woven mesh fabrics, this awning effectively reduces glare and UV without obstructing the outside view.

### Available Sizes

**Width:**

Maximum Width - 5800mm - open weave fabrics

**Drop:**

Maximum Drop - 3500mm - open weave fabrics

**Maximum Area under Warranty:**

20 square metres - open weave fabrics

### Headbox (optional)

**Material:**

Colourbond Steel (optional extra only - hood must be fitted cosmetically)

**Headbox Ends Material:**

Colourbond Steel

**Available Colours:**

Black, Dark Brown, Dark Green, Heritage Red, Merino, Mist Green, Mountain Blue, Primrose, Slate Grey, Wheat, White

### Top Roller Keyway Tube

**Material:**

Galvanised Steel

**Colour:**

Silver

**Available Sizes:**

63mm, 70mm, 78mm, 85mm diameter

### Pivot Pin And Plate

T304 Stainless Steel

### Drive End

Black Nylon 66 (5% Glass filled)

### Idle End With Hole

Black Nylon 66 (5% Glass filled)

### Gear Box Drive

Manual Gearbox 2.7 : 1 Ratio

**Available Colours:**

Charcoal or White

### Crank Handle

**Available Sizes:**

1000mm, 1200mm, 1600mm, 1800mm, 2200mm.

**Available Colours:**

Charcoal or White

### Installation Brackets

T304 Polished Stainless Steel

## Bottom Rail

Oval Silver Anodised Aluminium

---

## Bottom Rail Endcap Master And Guide

Black Nylon 66 (5% Glass filled)

---

## Lock Down Latch Set

Optional extra - Stainless steel latch set that slides into the bottom rail and clips into a D ring at the bottom of the awning

---

## Wire Cable

3.2mm diameter T316 Stainless Steel Cabling (19 X 1 construction)

---

## Top And Bottom Bush

T316 Stainless Steel

---

## Bottom Brackets

T304 Stainless Steel L Bracket - 75mm X 35mm X 25mm

---

## Deck Plate Assembly

T304 Stainless Steel

---

## Motorisation

240V AC: Somfy LT50 and LT60 tubular motors are mounted inside 63mm, 70mm, 78mm, 85mm roller tubes. Switch operated or remote control are available.

---

## Available Fabrics

Addalong Canvas, Brella Canvas, Hunter Douglas Canvas, Dickson, Planasol, Solaire, Docril, Sun Brella, Outlook, Vistaweave, Shadeview, Visiontex

---